Immersion


ARMTI-3 Solution Water **Applications**








- 2-1/2" NPT Stainless Steel **Screw Plug**
- INCOLOY® Sheath Elements
- · High Watt Density (46 53 W/ln²)
- 3 18 kW
- Integral Thermostat (DPST)
- · 240 and 480 Volt, Three Phase
- **General Purpose Terminal Enclosure**





Specifications and Ordering Information

							T2 — Temperature (60 - 250°F)			T1 — Temperature (0 - 100°F)		
kW	Volts	Phase	W/In²	No. Elem.	DIM B (In.)	Wt. (Lbs.)	Model	Stock	PCN	Model	Stack	PCN
E1 General Purpose ¹												
3	240 480	3	51 51	3 3	. 7 7	8 8	ARMTI-3305T2 ARMTI-3305T2	AS AS	188787 188824	ARMTI-3305T1 ARMTI-3305T1	AS AS	188795 188832
4.5 4.5	240 480	3	48 48	3	11	8 8	ARMTI-3455T2 ARMTI-3455T2	AS AS	188867 188904	ARMTI-3455T1 ARMTI-3455T1	AS AS	188875 188912
6	240 480	3	48 48	3	17-3/8 17-3/8	9	ARMTI-3605T2 ARMTI-3605T2	AS AS	188947 188980	ARMTI-3605T1 ARMTI-3605T1	AS AS	188955 188998
7.5 7.5	240 480	3	53 53	3	19 19	10 10	ARMTI-3755T2 ARMTI-3755T2	AS AS	189026 189069	ARMTI-3755T1 ARMTI-3755T1	AS AS	189034 189077
9	240 480	3	47 47	3,	24-3/8 24-3/8	10 10	ARMTI-3905T2 ARMTI-3905T2	AS AS	189106 189149	ARMTI-3905T1 ARMTI-3905T1	AS AS	189114 189157
12 12	240 480	3	46 46	3	32-1/4 32-1/4	11 11	ARMTI-3120T2 ARMTI-3120T2	AS AS	189181 189229	ARMTI-3120T1 ARMTI-3120T1	AS AS	189190 189237
15 15	240 480	3	46 46	3	39-7/8 39-7/8	12 12	ARMTI-3150T2 ARMTI-3150T2	AS AS	189261 189309	ARMTI-3150T1 ARMTI-3150T1	AS AS	189270 189317
18 18	240 480	3	51 51	33	47-3/8 47-3/8	13 13	ARMTI-3180T2 ARMTI-3180T2	AS AS	189341 189384	ARMTI-3180T1 ARMTI-3180T1	AS AS	189350 189392

Stock Status: S = stock AS = assembly stock NS = non-stock **To Order**—Specify model, volts, phase, kW, PCN and quantity.

- Heaters with General Purpose Enclosures are UL Listed and CSA Certified. Heaters with Moisture Resistant/Explosion Resistant Enclosures are CSA NRTL/C Certified.